

## SEDONA BY LYNX™ SERIES

# **42'' SEDONA BUILT-IN GRILL** WITH ROTISSERIE, 1 PROSEAR INFRARED BURNER AND 2 STAINLESS STEEL BURNERS (L700PSR)







### L700PSR PRODUCT OVERVIEW

- Precise power—one ProSear™ Infrared Burner and two Stainless Steel Burners combining to provide up to 69,000 BTU
- Consistent assurance—direct spark ignition with battery backup
- Perfect clarity—dual halogen grill surface lights
- Quick visibility—temperature gauge
- Easy opening—Lynx Hood Assist
- Ready rotisserie—dedicated single speed rotisserie 16,000 btu back burner, motor, spit rods, and forks
- Generous capacity—1,049 square inches of cooking surface (728 primary, 321 secondary)
- Beautiful illumination—blue-lit control knobs
- Steady performance—heat-stabilizing design
- Smooth opening—fluid rotation handle
- Premier platform—stainless steel grilling grates
- Steadfast durability—heavy-duty welded construction eliminates gaps where grease can collect





## L700PSR PRODUCT FEATURES

The Sedona by Lynx<sup>™</sup> Series is always evolving to be the best at something new. That philosophy is reflected in its features. We've refined these features to give you a grilling experience that's both simple and stunning.

**STAINLESS STEEL BURNERS** 

**ROTISSERIE SYSTEM** 

FOR MORE **INFORMATION ON** SEDONA BY LYNX™ SERIES **PRODUCT FEATURES**, PLEASE VISIT

LYNXGRILLS.COM



PROSEAR™ INFRARED BURNER



**EXPANSIVE GRILLING SURFACE** 



INTEGRATED ILLUMINATION



CUT-OUT DIMENSIONS: WIDTH: 41" / HEIGHT: 10" / DEPTH: 21.25"

SHIPPING DIMENSIONS: WIDTH 34" / HEIGHT 47" / DEPTH 30" SHIPPING WEIGHT: 240 POUNDS







PRODUCT TECHNICAL SPECIFICATIONS



COOKING CONFIGURATION: BUILT-IN GRILL WITH ROTISSERIE, 1 PROSEAR **INFRARED BURNER AND 2 STAINLESS STEEL BURNERS** 




**CERAMIC RADIANT BRIQUETTES** 



SPARK IGNITION SYSTEM




SEAMLESS WELDED CONSTRUCTION



LYNX HOOD ASSIST


#### **L700 ISLAND PREPARATION**




outlet must be located within 6' of the 2" hole.

\* 2" round hole must be located at rear of grill cutout. 120V GFI

**COUNTERTOP NOTCH DETAIL** 



#### **INSULATING JACKET**



Note: Insulating jacket required for all grills installed into a combustible enclosure. For natural gas grills, commends using ¾" gas lines. Side burners may be rotated 90 degrees. See installation manuals for details.

**IDLYNX** FOR EVEN MORE ON THIS PRODUCT AND OTHER COMPLIMENTARY LYNX PRODUCTS, VIST LYNXGRILLS.COM