

SEDONA BY LYNX™ SERIES

42" SEDONA BUILT-IN GRILL with 3 stainless steel burners and rotisserie (L700R)







L700R PRODUCT OVERVIEW

- Variable power—three Stainless Steel Burners combining to provide up to 69,000 BTU
- Consistent assurance—direct spark ignition with battery backup
- Perfect clarity—dual halogen grill surface lights
- Quick visibility—temperature gauge
- Easy opening—Lynx Hood Assist
- Ready rotisserie——dedicated single speed rotisserie 16,000 btu back burner, motor, spit rods, and forks
- Generous capacity—1,049 square inches of cooking surface (728 primary, 321 secondary)
- Beautiful illumination—blue-lit control knobs
- Steady performance—heat-stabilizing design
- Smooth opening—fluid rotation handle
- Premier platform—stainless steel grilling grates
- Steadfast durability—heavy-duty welded construction eliminates gaps where grease can collect





L700R PRODUCT FEATURES

The Sedona by Lynx[™] Series is always evolving to be the best at something new. That philosophy is reflected in its features. We've refined these features to give you a grilling experience that's both simple and stunning.



ROTISSERIE SYSTEM



EXPANSIVE GRILLING SURFACE



STAINLESS STEEL BURNERS



SPARK IGNITION SYSTEM



CERAMIC RADIANT BRIQUETTES



LYNX HOOD ASSIST



SEAMLESS WELDED CONSTRUCTION



INTEGRATED ILLUMINATION

L700 ISLAND PREPARATION

FOR MORE **INFORMATION ON** SEDONA BY LYNX™ SERIES **PRODUCT FEATURES**, PLEASE VISIT LYNXGRILLS.COM



CUT-OUT DIMENSIONS: WIDTH: 41" / HEIGHT: 10" / DEPTH: 21.25"

SHIPPING DIMENSIONS: WIDTH 34" / HEIGHT 47" / DEPTH 30" SHIPPING WEIGHT: 240 POUNDS




GAS REQUIREMENTS: SHIPS IN LIQUID PROPANE OR NATURAL GAS FROM FACTORY




ELECTRICAL REQUIREMENTS: INSTALLATION REQUIRES AN OUTDOOR 120V/15GFI ELECTRICAL OUTLET ADJACENT TO PRODUCT

COOKING CONFIGURATION: BUILT-IN GRILL WITH ROTISSERIE, 1 PROSEAR **INFRARED BURNER AND 2 STAINLESS STEEL BURNERS**




COUNTERTOP NOTCH DETAIL



outlet must be located within 6' of the 2" hole.

* 2" round hole must be located at rear of grill cutout. 120V GFI

INSULATING JACKET



Note: Insulating jacket required for all grills installed into a combustible enclosure. For natural gas grills, commends using ¾" gas lines. Side burners may be rotated 90 degrees. See installation manuals for details.

IDLYNX FOR EVEN MORE ON THIS PRODUCT AND OTHER COMPLIMENTARY LYNX PRODUCTS, VIST LYNXGRILLS.COM

PRODUCT TECHNICAL SPECIFICATIONS