



# OUTDOOR CABINETRY COLLECTION

BASE CABINETS, FILLER STRIPS, SIDE PANELS, BACK PANELS



*Locally supplied countertop required for all models*



## LYNX CABINETRY FEATURES

The Lynx Outdoor Stainless Steel Cabinetry for the Professional Line allows customers the ability to design their very own complete Lynx outdoor kitchen. Base cabinets will be available for 42" and 54" Lynx Professional Grills, Side Burners, Power Burners, and 24" Refrigeration.

- Ability and flexibility to create multiple custom installations including wall configurations against a house, masonry or stucco half-wall or freestanding island configurations
- Easy to install – can be quickly assembled over a weekend
- Constructed of heavy-duty stainless steel
- 30" deep cabinets; Adjustable height from 34½" – 35 7/8" with 4½" toe kick area
- Fully concealed door hinges, which can be adjusted for left or right swing
- Drawers equipped with full-extension slides
- Connecting holes in all cabinet bases allow easy wire and plumbing routing
- Heavy-duty adjustable legs
- Optional clip-on toe kicks included
- Accepts locally supplied non-combustible countertops
- Two-year full warranty



FOR A COMPLIMENTARY CUSTOM DESIGN FOR YOUR OUTDOOR KITCHEN, VISIT [LYNXGRILLS.COM/DESIGN-CENTER](http://LYNXGRILLS.COM/DESIGN-CENTER)

## THE COLLECTION

MODEL NUMBER	CABINET DESCRIPTION	FOR USE WITH	DIMENSIONS	SHIPPING WEIGHT
LBCG42SS	Base Cabinet - 42" W. Grill	Grills: L42R-3, L42TR, L42ATR	42 1/4" W. x 29 7/8" D. x 34 1/2" - 35 7/8" H.	235 (106.6)
LBCG54SS	Base Cabinet - 54" W. Grill	Grill: L54TR	54 1/4" W. x 29 7/8" D. x 34 1/2" - 35 7/8" H.	250 (113.4)
LBCSBSS	Base Cabinet - Side Burner	Side Burner: LSB2-2	14 1/2" W. x 29 7/8" D. x 34 1/2" - 35 7/8" H.	104 (47.2)
LBCPBSS	Base Cabinet - Power Burner	Power Burner: LPB	20 1/4" W. x 29 7/8" D. x 34 1/2" - 35 7/8" H.	160 (72.6)
LBCREFSS	Base Cabinet - Refrigeration	Refrigeration: LN24DWR, LN24REF	32" W. x 29 7/8" D. x 34 1/2" - 35 7/8" H.	125 (56.7)
LBCDW2SS	Base Cabinet - 1 Door/1 Drawer		18" W. x 29 7/8" D. x 34 1/2" - 35 7/8" H.	141 (63.7)
LBCDW3SS	Base Cabinet - 3 Drawer		18" W. x 29 7/8" D. x 34 1/2" - 35 7/8" H.	156 (70.8)
LBCSKSS	Base Cabinet - Sink	Locally supplied sink	24" W. x 29 7/8" D. x 34 1/2" - 35 7/8" H.	165 (74.8)
LBCTRSS	Base Cabinet - Trash		18" W. x 29 7/8" D. x 34 1/2" - 35 7/8" H.	145 (65.8)
LCF90SS	Corner Filler Strip - 90°	90° Cabinet Bends	3" W.** x 3/4" D. x 34 1/2" H.	5 (2.3)
LCF135SS	Corner Filler Strip - 135°	135° Cabinet Bends	3" W.** x 3/4" D. x 34 1/2" H.	5 (2.3)
LFLR4SS	Front Filler Strip - 4"W.	All Base Cabinets	4" W. x 3/4" D. x 34 1/2" H.	5 (2.3)
LFLR8SS	Front Filler Strip - 8"W.	All Base Cabinets	8" W. x 3/4" D. x 34 1/2" H.	9 (4.1)
LOCF90SS	Outer Corner Filler Strip - 90°	Corners with 90° Angles	33" W.** x 3/4" D. x 34 1/2" H. - 35 7/8" H.	75 (34.0)
LOCF135SS	Outer Corner Filler Strip - 135°	Corner with 135° Angles	15 1/2" W.** x 3/4" D. x 34 1/2" H. - 35 7/8" H.	30 (13.6)
LOCWF90SS	Outer Corner (Wall) Filler Strip - 90°	Corners with 90° Angles	31" W.** x 3/4" D. x 34 1/2" - 35 7/8" H.	75 (34.0)
LOCWF135SS	Outer Corner (Wall) Filler Strip - 135°	Corner with 135° Angles	14 1/2" W.** x 3/4" D. x 34 1/2" - 35 7/8" H.	30 (13.6)
LSP30SS	Side Panel	All Base Cabinets	28 1/8" W. x 3/4" D. x 29 5/8" H.	16 (7.3)
LBP14SS	Back Panel - Side Burner	LBCSB	14 1/4" W. x 3/4" D. x 30 3/4" H.	10 (3.7)
LBP18SS	Back Panel - Drawers/Trash	LBCDW2/LBCDW3/LBCTR	18" W. x 3/4" D. x 30 3/4" H.	12 (5.4)
LBP20SS	Back Panel - Power Burner	LBCPB	20 1/4" W. x 3/4" D. x 30 3/4" H.	15 (6.8)
LBP24SS	Back Panel - Sink	LBCSK	24" W. x 3/4" D. x 30 3/4" H.	17 (7.7)
LBP32SS	Back Panel - Refrigeration	LBCREF	32" W. x 3/4" D. x 30 3/4" H.	21 (9.5)
LBP42SS	Back Panel - 42"W. Grill	LBCG42	42 1/4" W. x 3/4" D. x 30 3/4" H.	25 (11.3)
LBP54SS	Back Panel - 54"W. Grill	LBCG54	54 1/4" W. x 3/4" D. x 30 3/4" H.	32 (14.5)
LBPFLR4SS	Back Filler Strip - 4"W.	LFLR4	4" W. x 3/4" D. x 34 1/2" H.	5 (2.3)
LBPFLR8SS	Back Filler Strip - 8"W.	LFLR8	8" W. x 3/4" D. x 34 1/2" H.	9 (4.1)

\*\*from inside of turn to next cabinet

### COMMON INSTALLATIONS

For actual assembly of individual cabinets, please refer to Lynx installation instructions.

### IN GENERAL

The cabinets have been designed to be easily installed by contractor or consumer. The cabinets are designed completely of stainless steel and provide a rich, contemporary look that complements Lynx outdoor appliances. The cabinets adjustable from 34-1/2" – 35-7/8" high where the toe kick area is 4-1/2". Locally supplied countertops must be mounted on top. The leveling legs on each cabinet allow for adjustments on uneven surfaces. The leveling legs allow for a minimum adjustment of 34-1/4" and a maximum of 36". Typically, the first cabinet is placed at the highest point and the other cabinets are leveled from there. To gain the most flexibility from the kitchen design, separate all appliances by at least one base cabinet or with available 4"W. or 8"W. fillers (LFLR4/LFLR8). Remember to account for the 8" minimum the rotisserie motor requires for installation when placing cabinets next to a grill base. All cabinets are 30" deep.

The cabinets can be installed against a house, a masonry, a stucco half-wall or freestanding in an island configuration. A stainless side panel (LSP30) is available to finish ends where a wall doesn't exist. Each cabinet is leveled using the attached leveling legs and then together. Choose a **non-combustible** countertop material of 1-1/4" (like granite, quartz, etc.) or more (other stone, tile, etc.). If the countertop is greater than 1-1/4" thick, you should use shims (not included) to install the appliance (grill, side burner, power burner) flush to the countertop. After the countertop is installed the appliances are placed in them and the kitchen is complete.

*Note: The full weight of the appliance must be set on the solid bottom support, including shims if necessary, and not supported by the countertop side trim.*

### AGAINST A NON-COMBUSTIBLE SURFACE

When installing a run of cabinets that includes a grill base against a non-combustible surface, the back of the cabinets should be at least 3" from the wall to insure meeting the grill specifications. When this is the case, a 4"W. back panel (LBPFLR4) along with a 30" Side Panel (LSP30) can be used to finish the end of the cabinet run. The LBPFLR4 is screwed into the back of the cabinet that ends the run and matches up against the LSP30.

### ISLAND INSTALLATIONS

The cabinets can also be installed in an island format. If desired, a half-wall can be built at the back and side panels (LSP30) can be used to finish the sides. All the cabinets will be lined up flush at the face, or a 3-sided half-wall could be built to eliminate the side panels.

Alternatively, islands can be finished with Lynx produced back panels. There are individual panels made to fit each individual cabinet offered by Lynx. The result is a smooth, custom fit finish.